



Series ML 170-450 DN25-40 PN160



Dimensions:

| type | ML 170 | ML 240 | ML 360 | ML 450 |
|-------------|--------|--------|---------|---------|
| connection | G 1 | | | |
| A | 288 | 338 | 418 | 523 |
| B | 260 | 310 | 390 | 495 |
| C | 350 | 400 | 480 | 585 |
| D | 28 | 28 | 28 | 28 |
| E | 70 | 70 | 70 | 70 |
| F | 112 | 112 | 112 | 112 |
| G | 46 | 46 | 46 | 46 |
| weight | 7,5 kg | 8,5 kg | 10,1 kg | 13,1 kg |
| volume tank | 0,7 l | 0,9 l | 1,2 l | 1,6 l |

| type | ML 170 | ML 240 | ML 360 | ML 450 |
|-------------|--------|--------|---------|---------|
| connection | G 1 ½ | | | |
| A | 300 | 350 | 430 | 535 |
| B | 265 | 315 | 395 | 500 |
| C | 350 | 400 | 480 | 585 |
| D | 35 | 35 | 35 | 35 |
| E | 75 | 75 | 75 | 75 |
| F | 116 | 116 | 116 | 116 |
| G | 63,5 | 63,5 | 63,5 | 63,5 |
| weight | 7,9 kg | 8,9 kg | 10,5 kg | 13,5 kg |
| volume tank | 0,7 l | 0,9 l | 1,2 l | 1,6 l |



1) Connection for the potential equalization, only for application in the explosive area.

Dimensions: mm

Designs and performance values are subject to change.



Powering Business Worldwide

Pressure Filter

Series ML 170-450

DN25-40 PN160

Description:

Pressure filter series ML 170-450 have a working pressure up to 160 bar. Pressure peaks can be absorbed with a sufficient safety margin. The ML-filter is in-line mounted.

The filter element consists of star-shaped, pleated filter material, which is supported on the inside by a perforated core tube and is bonded to the end caps with a high-quality adhesive. The flow direction is from outside to inside. Filter elements are available down to 5 $\mu\text{m}_{(c)}$. Finer filtration is available upon request.

For cleaning the stainless steel mesh element (see special leaflets 21070-4 and 39448-4) or changing the filter element, remove the filter bowl and take out the element. The mesh elements are not guaranteed to maintain 100% performance after cleaning.

Eaton filter elements are known for high intrinsic stability and an excellent filtration capability, a high dirt-retaining capacity and a long service life.

Eaton filter elements are available up to a pressure resistance of 160 bar and a rupture strength of Δp 250 bar.

Eaton filter can be used for petroleum-based fluids, HW emulsions, water glycols, most synthetic fluids and lubrication fluids. Consult factory for specific fluid applications.

The internal valve is integrated into the filter head. After reaching the bypass pressure setting, the bypass valve will send unfiltered partial flow around the filter.

The reversing valve provides another level of protection for the filter element. The reverse flow will not be filtered.

1. Type index:

1.1. Complete filter: (ordering example)

ML. 360. 10VG. HR. E. P. - G. 5. - - AE

| | | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|----|----|----|
| 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 | 11 | 12 |
|---|---|---|---|---|---|---|---|---|----|----|----|

- 1 | **series:**
ML = in-line filter-medium pressure range
- 2 | **nominal size:** 170, 240, 360, 450
- 3 | **filter-material:**
80G, 40G, 25G stainless steel wire mesh
25VG, 16VG, 10VG, 6VG, 3VG microglass
- 4 | **filter element collapse rating:**
30 = Δp 30 bar
HR = Δp 160 bar (rupture strength Δp 250 bar)
- 5 | **filter element design:**
E = single-end open
- 6 | **sealing material:**
P = Nitrile (NBR)
V = Viton (FPM)
- 7 | **filter element specification:**
- = standard
VA = stainless steel
IS06 = for HFC applications, see sheet-no. 31601
- 8 | **process connection:**
G = thread connection according to ISO 228
- 9 | **process connection size:**
5 = G 1
7 = G 1 1/2
- 10 | **filter housing specification:**
- = standard
IS06 = for HFC applications, see sheet-no. 31605
- 11 | **internal valve:**
- = without
S1 = with bypass valve Δp 3,5 bar
S2 = with bypass valve Δp 7,0 bar
R = reversing valve, $Q \leq 70,06$ l/min
- 12 | **clogging indicator or clogging sensor:**
- = without
AOR = visual, see sheet-no. 1606
AOC = visual, see sheet-no. 1606
AE = visual-electric, see sheet-no. 1615
VS5 = electronic, see sheet-no. 1619

To add an indicator to your filter, use the corresponding indicator data sheet to find the indicator details and add them to the filter assembly model code.

1.2. Filter element: (ordering example)

01E. 360. 10VG. HR. E. P. -

| | | | | | | |
|---|---|---|---|---|---|---|
| 1 | 2 | 3 | 4 | 5 | 6 | 7 |
|---|---|---|---|---|---|---|

- 1 | **series:**
01E. = filter element according to company standard
- 2 | **nominal size:** 170, 240, 360, 450
- 3 | - 7 | see type index-complete filter

Technical data:

| | |
|--------------------------|--|
| design temperature: | -10 °C to +100 °C |
| operating temperature: | -10 °C to +80 °C |
| operating medium | mineral oil, other media on request |
| max. operating pressure: | 160 bar |
| test pressure: | 229 bar |
| process connection: | thread connection according to ISO 228 |
| housing material: | AL; carbon steel |
| sealing material: | Nitrile (NBR) or Viton (FPM), other materials on request |
| installation position: | vertical |

Classified under the Pressure Equipment Directive 2014/68/EU for mineral oil (fluid group 2), Article 4, Para. 3.
 Classified under ATEX Directive 2014/34/EU according to specific application (see questionnaire sheet-no. 34279-4).

Pressure drop flow curves:

Filter calculation/sizing

The pressure drop of the assembly at a given flow rate Q is the sum of the housing Δp and the element Δp and is calculated as follows:

$$\Delta p_{assembly} = \Delta p_{housing} + \Delta p_{element}$$

$$\Delta p_{housing} = (\text{see } \Delta p = f(Q) - \text{characteristics})$$

$$\Delta p_{Element} (mbar) = Q \left(\frac{l}{min} \right) \times \frac{MSK}{10} \left(\frac{mbar}{l/min} \right) \times v \left(\frac{mm^2}{s} \right) \times \frac{p}{0,876} \left(\frac{kg}{dm^3} \right)$$

For ease of calculation our Filter Selection tool is available online at www.eatonpowersource.com/calculators/filtration/


Material gradient coefficients (MSK) for filter elements

The material gradient coefficients in PSI/GPM apply to mineral oil (HLP) with a density of 0,876 kg/dm³ and a kinematic viscosity of 30 mm²/s (139 SUS). The pressure drop changes proportionally to the change in kinematic viscosity and density.


| ML | VG | | | | | G | | |
|-----|-------|-------|-------|-------|-------|--------|--------|--------|
| | 3VG | 6VG | 10VG | 16VG | 25VG | 25G | 40G | 80G |
| 170 | 2,187 | 1,518 | 0,972 | 0,846 | 0,578 | 0,0685 | 0,0640 | 0,0438 |
| 240 | 1,685 | 1,170 | 0,749 | 0,652 | 0,446 | 0,0531 | 0,0496 | 0,0340 |
| 360 | 1,233 | 0,856 | 0,548 | 0,477 | 0,326 | 0,0388 | 0,0362 | 0,0248 |
| 450 | 0,907 | 0,630 | 0,403 | 0,351 | 0,240 | 0,0285 | 0,0266 | 0,0182 |

$\Delta p = f(Q)$ – characteristics according to ISO 3968

The pressure drop characteristics apply to mineral oil (HLP) with a density of 0,876 kg/dm³. The pressure drop changes proportionally to the density.



Symbols:



Spare parts:

| item | qty. | designation | dimension | | | | article-no. | |
|------|------|------------------------------------|--------------|------------|------------|------------|--------------------|--------------|
| | | | ML 170 | ML 240 | ML 360 | ML 450 | | |
| 1 | 1 | filter element | 01E.170... | 01E.240... | 01E.360... | 01E.450... | | |
| 2 | 1 | O-ring | 34 x 3,5 | | | | 304338 (NBR) | 304730 (FPM) |
| 3 | 1 | O-ring | 75 x 3 | | | | 302215 (NBR) | 304729 (FPM) |
| 4 | 1 | support ring | 81 x 2,6 x 1 | | | | 304581 | |
| 5 | 1 | clogging indicator visual | AOR or AOC | | | | see sheet-no. 1606 | |
| 6 | 1 | clogging indicator visual-electric | AE | | | | see sheet-no. 1615 | |
| 7 | 1 | clogging sensor electronic | VS5 | | | | see sheet-no. 1619 | |
| 8 | 1 | screw plug | 20913-4 | | | | 309817 | |

item 8 execution only without clogging indicator or clogging sensor

Test methods:

Filter elements are tested according to the following ISO standards:

| | |
|-----------|---|
| ISO 2941 | Verification of collapse/burst resistance |
| ISO 2942 | Verification of fabrication integrity |
| ISO 2943 | Verification of material compatibility with fluids |
| ISO 3723 | Method for end load test |
| ISO 3724 | Verification of flow fatigue characteristics |
| ISO 3968 | Evaluation of pressure drop versus flow characteristics |
| ISO 16889 | Multi-pass method for evaluating filtration performance |

North America

44 Apple Street
Tinton Falls, NJ 07724
Toll Free: 800 656-3344
(North America only)
Tel: +1 732 212-4700

Europe/Africa/Middle East

Auf der Heide 2
53947 Nettersheim, Germany
Tel: +49 2486 809-0

Friedensstraße 41
68804 Altlußheim, Germany
Tel: +49 6205 2094-0

An den Nahewiesen 24
55450 Langenlonsheim, Germany
Tel: +49 6704 204-0

China

No. 3, Lane 280,
Linhong Road
Changning District, 200335
Shanghai, P.R. China
Tel: +86 21 5200-0099

Singapore

4 Loyang Lane #04-01/02
Singapore 508914
Tel: +65 6825-1668

Brazil

Rua Clark, 2061 - Macuco
13279-400 - Valinhos, Brazil
Tel: +55 11 3616-8400

For more information, please

email us at filtration@eaton.com

or visit www.eaton.com/filtration

© 2015 Eaton. All rights reserved. All trademarks and registered trademarks are the property of their respective owners. All information and recommendations appearing in this brochure concerning the use of products described herein are based on tests believed to be reliable. However, it is the user's responsibility to determine the suitability for his own use of such products. Since the actual use by others is beyond our control, no guarantee, expressed or implied, is made by Eaton as to the effects of such use or the results to be obtained. Eaton assumes no liability arising out of the use by others of such products. Nor is the information herein to be construed as absolutely complete, since additional information may be necessary or desirable when particular or exceptional conditions or circumstances exist or because of applicable laws or government regulations.